

## Professional Speaker MD-112



### Specification

|                                |                                               |
|--------------------------------|-----------------------------------------------|
| Model                          | MD-112                                        |
| System Type                    | Front inverted phase type                     |
| Transducer                     | LF: 1x12" (Φ65mm Voice coil) Ferrite magnet   |
|                                | HF: 1x1.34" (Φ34mm Voice coil) Ferrite magnet |
| Impedance                      | 8Ω                                            |
| Rated Power                    | 300W AES                                      |
| Peak Power                     | 1200W                                         |
| Frequency Response             | 50Hz-19kHz (-10dB)                            |
| Sensitivity (1W/1M)            | 99dB                                          |
| Maximum SPL* (Continuous/Peak) | 124dB/130dB                                   |
| Directivity (HxV)              | 80°x 60°                                      |
| Input connector                | 2 x Neutrik Speakon NI4MP, 1 +1-              |
| Enclosure Matrial              | 15mm MDF                                      |
| Hanging Screws                 | M8 Screws                                     |
| Surface Treatment              | Black spot paint                              |
| Net Weight                     | 19 Kg                                         |
| Dimensios (WxDxH)              | 365 x 390 x 640 (mm)                          |

*\*Remark: Peak level at 1 m under half space conditions using pink noise with crest factor 4*